

Nepshaw Lane South, Morley, Leeds, LS277JQ Materials Testing Manager: D. J. Brockbank

t: 0113 393 9791

e: dale.brockbank@wyjs.org.uk www.wyjs.org.uk/materialstesting



TEST REPORT

Client: Gabriel

> Hjulmagervej 55 Postbox 59 DK-9100 Aalborg

Denmark

73534-01 (amended) **Entry No:**

Date received: 04/02/2016

Client's Description: Sample of fabric: Leaf, Colour: 60074 Light Grey

Test Required: Pilling in accordance with BS EN 14465 and Colour Fastness to Rubbing

In accordance with BS EN ISO 139: 2005 for a minimum of 24 hours at Conditioning:

65+/-4%, Relative Humidity, 20+/-2°C

Date Tests Completed: 05/04/2016

Pilling: BS EN ISO 12945-2: 2000 Load 415g

Rating After 2,000 rubs After 5,000 rubs

Colour Fastness to Rubbing: BS EN ISO 105-X12:2002

		<u>Dry</u>	<u>wet</u>
Staining:	Warp Way	5	5
	Weft Way	5	5
Change in colour:	Warp Way	5	5
	Weft Way	5	5

Note: Change in colour is not a requirement of the method but was carried out at the request of the client.

This is hereby certified to be a correct return of the tests made of the items referred to herein

Vivienne Brockbank Senior Technician

Date of original 05 April 2016 Date of amendment 12 April 2016

- Unless instructed otherwise by the client sample remnants will be disposed of after 28 days.
- Tests marked ^N in this certificate are not included in the UKAS Accreditation Schedule for this Laboratory. Tests marked ^F in this certificate are performed under the Laboratory's Flexible Scope of Accreditation. Tests marked ^S in this certificate have been subcontracted to another ISO17025 Accredited Laboratory.
- Opinions and interpretations expressed herein are outside the scope of UKAS accreditation.
- Uncertainty budgets for test methods contained within this report are available on request. This Certificate relates only to the sample received and, unless that sample has been drawn by the staff of this laboratory, or its agent, and endorsed accordingly, any application of the result to a bulk quantity or other material is entirely the responsibility of the client.



